

Turbo VM

The Turbo VM is specifically designed for verge mowing over sustained periods.

With front or rear mounted options in both 1.6m and 2.0m models there is a Turbo VM machine for every application. A single lever control option is available for added flexibility.

Key Features

- 1.6m or 2.0m cutting widths
- Plus 90° to minus 50° cowl angling
- Direct drive through twin pivoting gearboxes
- 750mm offset
- Cat II three point linkage
- New front mount option available
- MP44 boot flails or twisted shackle flails



Product Specification

Turbo VM	1600	2000
Width	1.6m / 5'4"	2.0m / 6'7"
Fully offset left or centre	750mm / 2'5"	750mm / 2'5"
Direct Drive System	Quad Power Drive Belts + 90° Gearbox x 2	Quad Power Drive Belts + 90° Gearbox x 2
PTO input (rpm)	1000	1000
No. of Bootee Flails	44	54
Tractor HP	90hp	125hp
Cowl Angle Movement	140° (+90° to -50°)	140° (+90° to -50°)
Weight	1180kg / 2601lbs	1250kg / 2756lbs
Front Mountable	○	○



Want to know more about the Turbo VM range?

Scan the QR code to the left with a smart phone or tablet and compatible app to instantly view the page.

Alternatively visit: www.bomford-turner.com/landscape/flail-mowers-and-toppers/turbo-mower-vm/